

1. Identification

Product identifier L'OREAL PARIS MEN EXPERT THERMIC RESIST ANTI-PERSPIRANT
Other means of identification
SDS number 21-96-0000176
Recommended use Personal care product used for cosmetic effect.
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information

US Address: L'Oreal USA Products, Inc
 133 Terminal Avenue
 Clark, NJ 07066
 USA

Canadian Address: L'Oreal Canada
 4895 rue Hickmore
 Ville St-Laurent, H4T 1K5
 Canada

Emergency Phone # : 1-800-535-5053 (International: 352-323-3500)
 In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further information: 1-732-499-2741

Poison Control # : 412-390-3326

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
 Gases under pressure Liquefied gas
Health hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ISOBUTANE		75-28-5	80
ALUMINUM CHLOROHYDRATE		1327-41-9	3

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Not available.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ALUMINUM CHLOROHYDRATE (CAS 1327-41-9)	TWA	1 mg/m3	Respirable fraction.
ISOBUTANE (CAS 75-28-5)	STEL	1000 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ALUMINUM CHLOROHYDRATE (CAS 1327-41-9)	TWA	2 mg/m3
ISOBUTANE (CAS 75-28-5)	TWA	1900 mg/m3 800 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Applicable for industrial settings only. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other

Applicable for industrial settings only. Wear suitable protective clothing.

Respiratory protection

Applicable for industrial settings only. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Material name: L'OREAL PARIS MEN EXPERT THERMIC RESIST ANTI-PERSPIRANT
882460 03 Version #: 01 Issue date: 10-27-2020

SDS US
3 / 8

Physical state	Liquid.
Form	Aerosol.
Color	White.
Odor	Characteristic.
Odor threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 212 °F (> 100 °C) (liquid)
Flash point	> 212.0 °F (> 100.0 °C) Closed Cup (liquid)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	> 1 (liquid)
Explosive properties	Not explosive.
Heat of combustion (NFPA 30B)	34.94 kJ/g
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Chlorine. Fluorine. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No adverse effects due to eye contact are expected.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not known.

Product	Species	Test Results
---------	---------	--------------

L'OREAL PARIS MEN EXPERT THERMIC RESIST ANTI-PERSPIRANT

Acute

Oral

ATEmix 3.958e+006 mg/kg

Components	Species	Test Results
------------	---------	--------------

ALUMINUM CHLOROHYDRATE (CAS 1327-41-9)

Acute

Dermal

LD50 Rat > 2000 mg/kg OECD 402

Inhalation

Aerosol

LD50 Rat > 5 mg/l, 4 h OECD 403

Oral

LD50 Rat 9187 mg/kg

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. No adverse effects due to skin contact are expected.

Irritation Corrosion - Skin

ALUMINUM CHLOROHYDRATE OECD 404
Result: Not Irritating
Species: Rabbit

Serious eye damage/eye irritation Due to partial or complete lack of data the classification is not possible. No adverse effects due to eye contact are expected.

Irritation Corrosion - Eye

ALUMINUM CHLOROHYDRATE OECD 405
Result: Not Irritating
Species: Rabbit

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization

ALUMINUM CHLOROHYDRATE OECD 406
Result: Not Sensitizing
Species: Guinea pig

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Mutagenicity

ALUMINUM CHLOROHYDRATE Result: In vitro and in vivo tests did not show mutagenic effects.

Carcinogenicity Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Reproductivity

ALUMINUM CHLOROHYDRATE 1000 mg/kg bw/d OECD 422
Result: NOAEL
Species: Rat

Specific target organ toxicity - single exposure Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure Due to partial or complete lack of data the classification is not possible.

ALUMINUM CHLOROHYDRATE 200 mg/kg bw/d OECD 422
Result: NOAEL
Species: Rat

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Further information The reference to any animal testing for individual constituents mentioned in this document is based on public, third-party data.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
ALUMINUM CHLOROHYDRATE (CAS 1327-41-9)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna > 200 mg/l, 48 h OECD 202
Fish	LC50	Danio rerio 100 - 500 mg/l, 96 h OECD 203
Other	EC50	Activated sludge of a predominantly domestic sewage > 1000 mg/l, 3 h OECD 209
<i>Chronic</i>		
Crustacea	NOEC	Ceriodaphnia dubia 3.8 mg/l, 8 d EPA 600/4-89/001
Fish	NOEC	Pimephales promelas 56.48 mg/l, 7 d

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)
ISOBUTANE 2.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code This product is ignitable (D001) RCRA hazardous wastes when intended for disposal.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

FINISHED GOODS

UN number UN1950
UN proper shipping name AEROSOLS, FLAMMABLE, Limited Quantity
Class 2.1
Packing group Not applicable.
Transport hazard class(es)
Label(s) Limited Quantity
Packaging exceptions 306
LTD QTY Net Inner Capacity 1.0 L

BULK

Not regulated as dangerous goods.

IATA**FINISHED GOODS**

UN number ID8000
UN proper shipping name CONSUMER COMMODITY
Class 9 - Class 9
Packing group Not applicable.
ERG Number 9L

BULK

Not regulated as dangerous goods.

IMDG**FINISHED GOODS**

UN number UN1950
UN proper shipping name AEROSOLS, FLAMMABLE, Limited Quantity
Class 2.1
Packing group Not applicable.
Environmental Hazards
Marine pollutant No.
Transport hazard class(es)
Label(s) Limited Quantity
EmS F-D, S-U
LTD QTY Net Inner Capacity 1.0 L

BULK

Not regulated as dangerous goods.

General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ISOBUTANE (CAS 75-28-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical

No (Exempt)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ISOBUTANE (CAS 75-28-5)

